

PRODUCT DATA

A.M.W.

Andrews Coatings Ltd
Carver Building
Littles Lane
Wolverhampton
West Midlands
WV1 1JY

Tel. 01902 429190

info@mathysdirect.co.uk
www.mathysdirect.co.uk

DESCRIPTION

Water dilutable cleaning liquid based on a nitrogenous organic derivative.

MAIN PROPERTIES

In depth impregnation - long lasting action - not film forming - odourless - non-toxic.

RECOMMENDED USES

Cleaning of bituminous substrates, walls and woodwork.

TECHNICAL DATA

Colour: Colourless
Density: 1,0 g/cm³
VOC-content: 0 g/l
Flashpoint: Inflammable

Drying times 20°C/50% r.h.
To recoat: 2 -3 days

Coverage

Theoretical: 4 - 8 m²/l
Practical: Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Apply on a dry substrate. Brush off roofs or walls that are strongly soiled or moss-covered and clean with the appropriated products. Apply AMW abundantly, by preference with brush and wait 2 to 3 days. Then, brush dry and dust off or, if possible, clean with high-pressure water. Let dry and apply the paint system.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION & THINNING

Brush: Apply undiluted.

Cleanup: Water.

APPLICATION CONDITIONS

> 5°C and max. 90% R.H.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.