

PRODUCT DATA

PAINT STRIPPER DK 20 S

Andrews Coatings Ltd
Carver Building
Littles Lane
Wolverhampton
West Midlands
WV1 1JY

Tel. 01902 429190

info@mathysdirect.co.uk
www.mathysdirect.co.uk

DESCRIPTION

RUST-OLEUM® Paint Stripper DK 20 S is a highly effective paint dissolving/lifting material based on methylene chloride.

RECOMMENDED USES

RUST-OLEUM Paint Stripper DK 20 S should be used for quick removal of layers of old paint, oil and grease from metal, mineral and wooden surfaces. Paint Stripper DK 20 S is intended to remove all types of oil- and alkyd-based paints, emulsion paints, varnish and most two-component materials. As Paint Stripper DK 20 S does not contain acids or alkali's, it will not affect metal, mineral or wooden substrates.

TECHNICAL DATA

Appearance: Clear, thixotropic layer
Composition: Special blend of solvents and paraffin wax
VOC-content: 110 g/l

Coverage

Theoretical: 300 - 500 g/m² ≈ 2 - 4 m²/l.
Practical: Practical usage depends on many factors such as type and amount of contaminants, shape of the substrate and material losses during application.

DIRECTION FOR USE

Remove loose coatings as much as possible by scraping.
To release possible pressure open the can carefully.
Apply RUST-OLEUM Paint Stripper DK 20 S thickly with soft, long-hair natural brushes. Do not use synthetic brushes.
Allow to stand for 10 to 15 minutes, and remove the old layer with a filling knife or paint scraper.
Thick layers of some (two-component) products may need an additional treatment.
After use, clean the surface with a cleaner (f.e. ND 14), high pressure (steam) cleaning, fresh water or white spirit and allow to dry completely before applying a coating.
Clean the brushes with plenty of water. Never use in the vicinity of fire, hot surface or welding. Do not smoke. Use only in well-ventilated areas.

APPLICATION CONDITIONS

Temperature of air, substrate and material between 5 and 35°C and relative humidity below 85%.

REMARKS

RUST-OLEUM Paint Stripper DK 20 S may affect plastic materials alike e.g. PVC, polystyrene. In case of doubt, try on a small test patch beforehand. Although RUST-OLEUM Paint Stripper DK 20 S is based on methylene chloride, which is (in itself) non flammable, it may decompose forming toxic gases, if exposed to fire or extreme heat.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

1 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.