www.mathysdirect.co.uk

RUST-OLEUM MATHYS

best solutions in paints & coatings

PRODUCT DATA

PEGACRETE

DESCRIPTION

Powdered repair product on cement base and resins.

MAIN PROPERTIES

Quick hardening - good mechanical strength - 100 % shrink-resistant.

RECOMMENDED USES

For indoor and outdoor works.

For levelling and repairing cracks, holes and other damages in concrete, cement renderings and not painted brickwork.

TECHNICAL DATA

Appearance: Powdery (before mixing)

Colour: Grey
Density: 1,6 g/cm³

Mixing ration: 3,5 I Pegacrete has to be added to 1 I water

25 kg Pegacrete has to be added to 5 I water

Recommended film thickness: Wet film: 2 cm (cons.: 32 kg/m²)

Dry film: 2 cm (cons.: 32 kg/m²)

VOC-content: 0 g/l

Flashpoint: Not flammable

Pressure strength: 100 g Pegacrete + 20 g water Pressure resistance: 38 N/mm² (Orex, report B-I/6678).

Drying times 20°C/50% r.h.

To recoat: 2 days Full hardness 1 month

Coverage

Theoretical: Max. 32 kg/m² per coat

Practical: Practical coverage depends on many factors such as porosity and

roughness of the substrate and material losses during application.

SURFACE PREPARATION

On bare substrate: clean with steel brush or sand blaster.

The substrate must be solid and free from dust, oil and grease.

Porous substrates must be moistened first.

Metal parts are to be treated with Noxyde anti-rust.

APPLICATION & THINNING

Tools: Filling blade or trowel.

Cleanup: Water.

APPLICATION CONDITIONS

Apply at a temperature of min. 5°C.

REMARKS

- Do not use more water than necessary for the application.
- Add Pegacrete progressively to water and mix steadily.

Page: 1 / 2 PDS Pegacrete-gb / TE-52 Uitgave: 06-04-05 / Ver. 00 The information contained herein is given in good faith. However, since application conditions are beyond our control, N.V. Martin Mathys S.A. cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

Tel. 01902 429190

Andrews Coatings Ltd

Carver Building Littles Lane Wolverhampton West Midlands WV1 1JY

info@mathysdirect.co.uk www.mathysdirect.co.uk

www.mathysdirect.co.uk

RUST-OLEUM MATHYS

best solutions in paints & coatings

PRODUCT DATA

PEGACRETE

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

1 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Andrews Coatings Ltd

Carver Building Littles Lane Wolverhampton West Midlands WV1 1JY

Tel. 01902 429190

info@mathysdirect.co.uk www.mathysdirect.co.uk