

PRODUCT DATA

PLASTOPAN LATEX

Andrews Coatings Ltd
Carver Building
Littles Lane
Wolverhampton
West Midlands
WV1 1JY

Tel. 01902 429190

info@mathysdirect.co.uk
www.mathysdirect.co.uk

DESCRIPTION

Water-based extra white putty/filler.

MAIN PROPERTIES

Easy to apply - easy to sand - can be applied on alkaline substrates.

RECOMMENDED USES

For equalising inside walls before applying a latex coating.

TECHNICAL DATA

Appearance:	Flat
Colour:	White
Density:	± 1,9 g/cm ³
Solids Content:	In volume: ± 63%
	In weight: ± 80%
Recommended film thickness:	Wet film: ± 1,6 mm (cons.: 3 kg/m ²)
	Dry film: ± 1,0 mm (cons.: 3 kg/m ²)
Flashpoint:	Not flammable
VOC-content:	Max. 15.2 g/l

Drying times	20°C/50% r.h.
To recoat:	24 hours

Coverage

Theoretical:	± 3 kg/m ²
Practical:	Depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Clean the substrate thoroughly. Remove old and loose coating layers. Do not apply on powdering and chalking layers. Can be applied without applying a primer.

THINNING AND APPLICATION

Putty knife: Apply without thinning.

Cleaning: Water.

APPLICATION CONDITIONS

Apply in a dry and well-ventilated area.

REMARKS

Apply Plastopan Latex in thin layers.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cartridges, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.