

PRODUCT DATA

SECCO SUPER

Andrews Coatings Ltd
Carver Building
Littles Lane
Wolverhampton
West Midlands
WV1 1JY

Tel. 01902 429190

info@mathysdirect.co.uk
www.mathysdirect.co.uk

DESCRIPTION

Water repellent product based on polysiloxanes.

MAIN PROPERTIES

Water repellent - water vapour permeable (breathing) - colourless - does not change the colour of the substrate - may be applied on dry recent masonry.

RECOMMENDED USES

Water repellent treatment of porous walls (bricks, concrete, cement, etc.).

TECHNICAL DATA

Colour:	Colourless
Density:	± 0,8 g/cm ³
Solids Content:	In volume: ± 5% In weight: ± 5%
VOC-content:	Max. 790 g/l
Flashpoint:	> 39°C

Coverage

Theoretical:	1 - 4 m ² /l
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Clean and dust off the outside walls that are sufficiently dry. Cracks and fissures must be filled up first.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION & THINNING

Brush:	Apply undiluted until saturation (= wet outlook during a few seconds); it is advisable to apply a second coat within 15 minutes to obtain an optimum impregnation.
Roller:	Apply with woollen roller with long hairs. Do not dilute.
Air-atomised spray:	Not recommended. Can be flowed on the substrate with hand pressure equipment after removing the nozzle.
Airless spray:	Not recommended.
Cleanup:	White spirit.

APPLICATION CONDITIONS

Dry weather, outside walls to be as dry as possible.

REMARKS

- Non-porous surfaces (glass, blue stone, varnished brick, etc.) must be protected from spray mist or spatters of Secco.
- Apply Secco only on non-painted mineral or cement containing substrates. The substrate has to be porous.
- Can be recovered with Murfill or Paracem.

PRODUCT DATA

SECCO SUPER

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Andrews Coatings Ltd

Carver Building
Littles Lane
Wolverhampton
West Midlands
WV1 1JY

Tel. 01902 429190

info@mathysdirect.co.uk
www.mathysdirect.co.uk