

MATHYS DAC HYDRO PLUS

WATER BASED ROOF TILE PAINT



Make roof tiles look like new again

Simple, quick and cost effective

Flexible and durable acrylic paint for renovation and protection of various roof tiles (see overview below). Dac Hydro-Plus is weather resistant, micro porous, elastic, easy to apply and has a durable finish that combines nice aesthetics with a long-lasting gloss retention.

9 m²/L

- Quick, easy and affordable
- Creates an impermeable water barrier
- Micro-porous, so water vapour-permeable
- Long-lasting gloss retention
- Theoretical coverage: 9-11 m²/litre per layer
- Waterproof after 2 hrs., recoatable after 24 hrs.

Tile type	Primer	Topcoat (DAC Hydro® Plus)
Concrete tile	-	2 coats
Fibrous tile (porous) Worn Eternit*	Pegafix® or Primer 44HS	2 coats
Fibrous tile (sound) New Eternit	-	2 coats
Slate tile	Pegafix® or Primer 44HS	2 coats
Terracotta tile, Redland tile	Primer 44HS	2 coats
All other weathered and/or very absorbent tiles	Primer 44HS	2 coats
Very closed substrates (e.g. varnished or enamelled tiles)	Noxyde® diluted with 25% water	2 coats

*It is not recommended to apply Dac Hydro Plus on artificial slates of the Eternit type that are too strongly deteriorated.


These guidelines are provided for information purposes only. Since the manufacturer is unable to exercise any control over the correct application and processing of the products, he cannot accept any responsibility for this. See product datasheet for further information (www.rustoleum.eu)

Technical reference


	Water based
Coverage:	9-11 m ² /l.
Dry to touch:	1 hr
Dry to recoat:	24 hrs
Colours:	See colour card
Pack sizes:	4L, 15L
Substrates:	Different roof tiles, see system selector
Recoatable with:	Not applicable



Standard colours Dac Hydro D (Satin Matt) and Dac Hydro Plus (Matt)



C859 - Black




C355 - Tile red



D276 - Redbrown



C351 - Slate grey



C353 - Brown



E596 - Rustic