

# MATHYS **DACFILL** WATERPROOFING

**A ready-to-use waterbased liquid membrane for roofs**

- Waterborne , super-elastic, 100% watertight
- Resistant to UV radiation, acid rain, heat, frost and pollution
- Easy to apply with a brush, roller or airless spray
- For roofs and chimney slabs (min. slope of 1%)
- Barely flammable and self-extinguishing
- Can be mechanically reinforced with Dacfill-fleece



## ***Excellent watertightness, quickly!***

**Forms a lasting rubber-like coat without joints or seams on all types of roofs with slope of minimal 1%.**



Approved for asbestos encapsulation.

**Standard colours:**



Available in almost any colour upon request.  
Note: Minor differences between above printed and supplied colours are possible due to printing limitations.



Extra mechanical strength can be obtained by using reinforcement fleeces.

### Technical reference

	Water based
<b>Coverage:</b>	0.6 – 3 kg/m <sup>2</sup> (see product datasheet)
<b>Dry to touch:</b>	2 hr
<b>Dry to recoat:</b>	24 hrs
<b>Colours:</b>	See colour card
<b>Pack sizes:</b>	1kg, 5kg, 25kg
<b>Substrates:</b>	Sloped roofs (roofing, bituminous), chimney slabs, Primer 44HS, diluted Noxyde®
<b>Recoatable with:</b>	Dac Hydro Alu, Coating PRT