

# 5090

## ANTI CONDENSATION


**Mould-resistant anti-condensation coating**

**For ceilings and the upper part of walls**  
**Prevents dripping from condensation**

- Water-based
- Recoatable after just 5 hours
- Application on slightly damp surfaces
- Ideal for high humidity areas (breweries, wash and shower rooms, etc.)

### Technical reference

	Water based
<b>Coverage:</b>	5.4 m <sup>2</sup> /l. at 50 µm dry
<b>Dry to touch:</b>	1 hr
<b>Dry to recoat:</b>	5 hrs
<b>Colours:</b>	Off white
<b>Pack sizes:</b>	5L, 20L
<b>Substrates:</b>	Ceilings and upper parts of walls.
<b>Recoatable with:</b>	Itself



GENERAL

METAL  
General Purpose

METAL  
Noxydizing™

METAL  
Cladding Solutions

FLOORS

EXTERIOR WALLS

ROOFS

HYGIENE

TECHNICAL

# DAKFILL FRIGO

## GAS & VAPOUR TIGHT

**Gas & vapour tight coating for walls and ceilings**

**Builds an abrasion resistant rubberlike coat without joints or seams which is hardly flammable and self-extinguishing (DIN 4102).**

**IDEAL FOR COLD STORES**

- Solvent free formula
- Permanent high elasticity (> 400%)
- Resistance against sudden variations in temperature
- High mechanical strength
- Does not contain bituminous products

### Technical reference

	Solvent free
<b>Coverage:</b>	2-3 kg/m <sup>2</sup>
<b>Dry to touch:</b>	1,5 hr
<b>Dry to recoat:</b>	24 hrs
<b>Colours:</b>	White
<b>Pack sizes:</b>	25 Kg
<b>Substrates:</b>	Directly on insulation material such as polystyrene foam, polyurethane. On concrete, bricks, wood, zinc, aluminium, primers Pegafix® or Primer 44HS.
<b>Recoatable with:</b>	Not applicable

