

5090

ANTI CONDENSATION


Mould-resistant anti-condensation coating

For ceilings and the upper part of walls
Prevents dripping from condensation

- Water-based
- Recoatable after just 5 hours
- Application on slightly damp surfaces
- Ideal for high humidity areas (breweries, wash and shower rooms, etc.)

Technical reference

	Water based
Coverage:	5.4 m ² /l. at 50 µm dry
Dry to touch:	1 hr
Dry to recoat:	5 hrs
Colours:	Off white
Pack sizes:	5L, 20L
Substrates:	Ceilings and upper parts of walls.
Recoatable with:	Itself



GENERAL

METAL
General Purpose

METAL
Noxydizing™

METAL
Cladding Solutions

FLOORS

EXTERIOR WALLS

ROOFS

HYGIENE

TECHNICAL

DAKFILL FRIGO

GAS & VAPOUR TIGHT

Gas & vapour tight coating for walls and ceilings

Builds an abrasion resistant rubberlike coat without joints or seams which is hardly flammable and self-extinguishing (DIN 4102).

IDEAL FOR COLD STORES

- Solvent free formula
- Permanent high elasticity (> 400%)
- Resistance against sudden variations in temperature
- High mechanical strength
- Does not contain bituminous products

Technical reference

	Solvent free
Coverage:	2-3 kg/m ²
Dry to touch:	1,5 hr
Dry to recoat:	24 hrs
Colours:	White
Pack sizes:	25 Kg
Substrates:	Directly on insulation material such as polystyrene foam, polyurethane. On concrete, bricks, wood, zinc, aluminium, primers Pegafix® or Primer 44HS.
Recoatable with:	Not applicable

